

TECHNICAL SPECIFICATIONS
SEAT Arona



	1.0 TSI 95PS	1.0 TSI 115 PS	1.0 TSI 115 PS DSG
ENGINE			
Cylinder/Valve (Total)	3 Cyl. - 12v		
Displacement (cc)	999		
Bore and stroke (mm)	74,5 X 76,4		
Compression ratio	10,5		
Maximum power (Kw/hp/rpm)	70/95/ 5000-5500	85/115/ 5000-5500	
Max. Torque (NM/rpm)	175/2000-3500	200 / 2000-3500	
Fuel supply system	TSI-Direct Injection		
Ignition	Positiv Ignition (Electronic map-controlled ignition)		
Fuel type	ROZ 95		
Emissions standard	EU6		
Alternator (A)	110A		
Battery (Ah)	59 Ah		
PERFORMANCE			
Max. Speed (Km/h)	173	182	182
Acceleration 0-100 km/h	11,6	9,8	10,0
MASS EMISSION			
CO2 Combined (g/Km)	112	114	114
FUEL CONSUMPTION			
Combined (l/100 Km)	4,9	4,9 / 5,0	5,0
TRANSMISSION			
Gearbox type:	Manual 5-speed	Manual 6-speed	DSG 7-speed
I	3,769	3,769	3,765
II	1,955	1,955	2,273
III	1,281	1,281	1,531
IV	0,881	0,973	1,133
V	0,673	0,778	1,176
VI	-	0,642	0,956
VII	-	-	0,795
R	3,181	3,181	4,167
Group ratio	4,357 (1)	4,056 (1)	4,778 (1) - 3,583 (2) - 4,526 (3)
Speed 1000 rpm in IV/V/VI (km/h)	31,2 / 40,9	30,4 / 38,0 / 46,1	22,1 / 28,4 / 34,9 / 42
CHASIS			
Front suspension	Independent type McPherson - coil springs - hydraulic shock absorber		
Rear suspension	Semirigid axle, coil springs and hydraulic shock absorber		
Steering system	C - EPS		
Turning diameter (m)	10,6		
Front / Rear brake type	Ventilated front brakes / Drum-Disc brakes in rear axle	Ventilated front brakes / Disc brakes in rear axle	
Front brakes (mm)	276x24		276x24
Rear brakes (mm)	228x42	230x9	230x9
Rims (")	16" - 17" - 18"		
Tyres	205/60 R16 - 205/55 R17 - 215/45 R18		
PACKAGE			
Body type	SUV 5 doors		
Length / width / height (mm)	4138 / 1780 / 1552		
Wheelbase (mm)	2566		
Front/Rear track (mm)	1503 / 1486		
Boot capacity (L)	400		
Petrol tank capacity (L)	40		
WEIGHTS			
In running order with driver (Kg)	1165	1187	1210
Max. Weight allowed (Kg)	1615	1625	1645

TECHNICAL SPECIFICATIONS
SEAT Arona



	1.5 TSI Evo 150PS
ENGINE	
Cylinder/Valve (Total)	4 Cyl. - 16 v
Displacement (cc)	1498
Bore and stroke (mm)	74,5 x 85,9
Compression ratio	10,5
Maximum power (Kw/hp/rpm)	110/150 / 5000-6000
Max. Torque (NM/rpm)	250 / 1500-3500
Fuel supply system	Direct Injection
Ignition	Positiv Ignition (Electronic map-controlled ignition)
Fuel type	ROZ 95
Emissions standard	EU6
Alternator (A)	110A
Battery (Ah)	59Ah
PERFORMANCE	
Max. Speed (Km/h)	205
Acceleration 0-100 Km/h (s)	8,0
MASS EMISSION	
CO2 Combined (g/Km)	118
FUEL CONSUMPTION	
Combined (l/100 Km)	5,1
TRANSMISSION	
Gearbox type:	Manual 6-speed
I	4,111
II	2,118
III	1,36
IV	1,029
V	0,857
VI	0,733
VII	-
R	3,999
Group ratio	3,647 (1)
Speed 1000 rpm in IV/V/VI (km/h)	31,9 / 38,3 / 44,8
CHASIS	
Front suspension	Independent type McPherson - coil springs - hydraulic shock absorber
Rear suspension	Semirigid axle, coil springs and hydraulic shock absorber
Steering system	C - EPS
Turning diameter (m)	10,6
Front / Rear brake type	Ventilated front brakes / Disc brakes in rear axle
Front brakes (mm)	276x24
Rear brakes (mm)	230x9
Rims (")	17" - 18"
Tyres	205/55 R17 - 215/45 R18
PACKAGE	
Body type	SUV 5P
Length / width / height (mm)	4138 / 1780 / 1552
Wheelbase (mm)	2566
Front / Rear track (mm)	1503 / 1486
Boot capacity (L)	400L
Petrol tank capacity (L)	40
WEIGHTS	
In running order with driver (Kg)	1222
Max. Weight allowed (Kg)	1665

TECHNICAL SPECIFICATIONS
SEAT Arona



	1.6 TDI 95 PS	1.6 TDI 95 PS	1.6 TDI 115 PS
ENGINE			
Cylinder/Valve (Total)	4 Cyl. - 16v		
Displacement (cc)	1598		
Bore and stroke (mm)	79,5 X 80,5		
Compression ratio	16,2		
Maximum power (Kw/hp/rpm)	70/95 / 2750-4600		85/115 / 3250-4000
Max. Torque (NM/rpm)	250 / 1500-2600		250 / 1500-3200
Fuel supply system	Direct injection: Common Rail		
Ignition	Compressed ignition		
Fuel type	DIESEL		
Emissions standard	EU6		
Alternator (A)	110A / 140A		
Battery (Ah)	70Ah		
PERFORMANCE			
Max. Speed (Km/h)	172	174	185
Acceleration 0-100 Km/h (s)	11,8	11,7	10,1
MASS EMISSION			
CO2 Combined (g/Km)	107	106	108
FUEL CONSUMPTION			
Combined (l/100 Km)	4,1		
TRANSMISSION			
Gearbox type:	Manual 5-speed	DSG 7-speed	Manual 6-speed
I	3,778	3,5	4,111
II	1,944	2,087	2,118
III	1,185	1,343	1,36
IV	0,816	0,933	0,971
V	0,625	0,974	0,773
VI	-	0,778	0,625
VII	-	0,653	-
R	3,600	3,721	3,999
Group ratio	3,647 (1)	4,8 (1) - 3,429 (2) - 4,5 (3)	3,389 (1)
Speed 1000 rpm in IV/V/VI (km/h)	40,3 / 52,5	26,7 / 35,8 / 44,9 / 53,5	36,4 / 45,7 / 56,5
CHASSIS			
Front suspension	Independent type McPherson - coil springs - hydraulic shock absorber		
Rear suspension	Semirigid axle, coil springs and hydraulic shock absorber		
Steering system	C-EPS (Column Electric Power System)		
Turning diameter (m)	10,6		
Front / Rear brake type	Ventilated front brakes / Drum-Disc brakes in rear axle		
Front brakes (mm)	276x24		
Rear brakes (mm)	228x42		230x9
Rims (")	16" - 17" - 18"		
Tyres	250/60 R16 - 205/55 R17 - 215/45 R18		
PACKAGE			
Body type	SUV 5 doors		
Length / width / height (mm)	4138 / 1780 / 1552		
Wheelbase (mm)	2566		
Front/Rear track (mm)	1503 / 1486		
Boot capacity (L)	400		
Petrol tank capacity (L)	40		
WEIGHTS			
In running order with driver (Kg)	1297	1320	1303
Max. Weight allowed (Kg)	1715	1745	1725

* The data used in this report are preliminary